

# Microbus MicroLED

COB 16:9 - 27"



- *Dark matte surface*
- *Seamless design*
- *120 fps, 3840Hz*
- *High resolution*
- *DCI-P3 Wide colour gamut*

*Next generation seamless MicroLED with anti-glare surface for deeper blacks and richer colour vibrancy. Features pro reference modes for HDR colour grading.*

<b>SPECIFICATIONS</b>	<b>0,7mm</b>	<b>0,9mm</b>	<b>1,2mm</b>	<b>1,5mm</b>	<b>1,8mm</b>
Dimensions <sup>(WxDxD)</sup>	600 x 337.5 x 39 mm				
Weight	4.5 kg				
Resolution	768 x 432 px	640 x 360 px	480 x 270 px	384 x 216 px	320 x 180 px
Aspect Ratio	16:9				
Brightness	600 nits				
Contrast Ratio	10,000:1				
Refresh Rate	3 840 Hz				
Frame Frequency	Up to 120 fps				
Viewing Angle	≥ 165 °				
Color Temperature	2,500 ~ 10,000 K				
Power Consumption <sup>(Avg/Max)</sup>	28-85 W	27-81 W	25-73 W	24-70 W	22-69 W
Working Voltage	AC: 100V ~ 240V, 50-60Hz				
Lifetime	100,000 h				
IP Rating	IP54				
Operating temperature	-20° ~ +60° C				
Humidity Range	10 ~ 90				